



New



Blis round



Blis square



Blis rectangular



Technical Information

Version	Blis round	Blis square	Blis rectangular
Power	15W	15W	24W
Installation	Surface	Surface	Surface
Color Temperature	Switch 2.700K / 3.200K / 4.000K	Switch 2.700K / 3.200K / 4.000K	Switch 2.700K / 3.200K / 4.000K
Lumens	1.470 lm	1.370 lm	2.360 lm
Material	Polycarbonate	Polycarbonate	Polycarbonate
Finishes	White / Black / Corten	White / Black / Corten	White / Black / Corten

Code	Blis round	Blis square	Blis rectangular
	4957 <input type="checkbox"/>	4960 <input type="checkbox"/>	4982 <input type="checkbox"/>
	4958 <input checked="" type="checkbox"/>	4961 <input checked="" type="checkbox"/>	4983 <input checked="" type="checkbox"/>
	4959 <input checked="" type="checkbox"/>	4962 <input checked="" type="checkbox"/>	4984 <input checked="" type="checkbox"/>

PF >0,6 | 250°

PF >0,6 | 180°

PF >0,9 | 180°



*IP65 connection box included.

3 YEARS WARRANTY | 25.000 HOURS | IP 65 | 220/240 VAC | CRI ≥80 | | 50/60 Hz | | +40°C / -20°C | CCT SWITCH |